

GT 2000



Tecnoma



GT 2000

Precision with simplicity

Corrosion resistant robust chassis

- Welded chassis painted with highly resistant powder paint coating.
- Slimline straight and narrow drawbar, adjustable in height.
- Adjustable Jack.
- Operator platform for easy tank access.
- 9.5 R 44 tyres.
- Parking brake.



High output pump



Pump PM 300

- PM 300 piston diaphragm pump, 135 l/mn, 15 bars maximum pressure.
- Standard suction filter and pressure filters.

Robust and easy to maintain sprayer tank

- High density rotomoulded polyethylene tank, 2000 litres capacity.
- 400 mm lid with strainer (500 microns) and mixing mushroom.
- Hydraulic tank agitation.
- Transparent tank gauge.
- 150 litres rinsing tank.
- 15 litres hand wash tank.
- Optional chemical induction hopper.



Optional Lav/ton



Optional induction hopper with can wash and rinse ring



Easily visible tank and pressure gauges



Rinsing and hand wash tanks

Choice of two sprayer controllers

REGULAIR : air pressure at your finger tips

High accuracy air pressure regulator with built in boom section pressure compensation. REGULAIR increases operator comfort thanks to its air assistance. On-the-go dosage adjustment is controlled from finger tip by mean of ergo joystick handle and electric valves. Compensated return free distribution for accurate spray applications.



Regulair Ergo joystick handle



TECNOMA solenoid valve

AXIS rate governor: accuracy without complication

Electronic DPA flow controller, using a flowmeter. Simple and easy dial a flow controller.

AXIS controller offers outstanding ergonomic and real ease of use for the operator.

Distribution is carried out by mean of TECNOMA solenoid valves.



AXIS controller

A wide range of booms

- Hydraulic folding booms with hydraulic lift.
- Albatross pendulum suspension with nitrogen gas strut for unmatched stability.
- Spraying circuit fitted with Rotoflex and Pentajet equipped with diaphragm check valves.
- Optional tilt correction.



Pentajet

> GDM : from 12 to 18 metres

Fully hydraulic rear folding boom, single side fold.

> HLE : from 15 to 21 metres

Fully hydraulic lateral folding boom with simultaneous opening of both sides.

Tecnoma 
technologies

S.A.S. - Capital 1 174 400 euros - R.C.S. EPERNAY B 350 484 309
54, rue Marcel Paul - F-51206 EPERNAY CEDEX
Tél. : (33) 03.26.51.99.99 - Fax (33) 03.26.51.83.51
Site : www.tecnoma.com - E-mail : tecnoma@tecnoma.com